Samsung SSD 850 EVO mSATA

Data Sheet Rev.2.0 (May 2016)



Summary

- SATA 6Gb/s SSD for Client PCs
- mSATA
- Samsung V-NAND
- Samsung Magician Software for SSD management
- Samsung Data Migration Software

V-NAND Technology and THE SAMSUNG SSD 850 EVO Series

Samsung's unique and innovative V-NAND flash memory architecture is a breakthrough in overcoming the density limitations, performance and endurance of today's conventional planar NAND architecture. V-NAND is fabricated by stacking cell layers vertically over one another rather than decreasing the cells dimensions and trying to fit itself onto a fixed horizontal space resulting in higher density and better performance utilizing a smaller footprint.

The 850 EVO Series is the advanced consumer SSD powered by V-NAND technology that maximizes everyday computing experiences with optimized performance and enhanced reliability.

Optimized performance for everyday computing experiences

Powered by Samsung's cutting-edge V-NAND technology, the 850 EVO mSATA delivers top-class sequential and random read and write performance to optimize everyday computing experiences.

The 850 EVO mSATA is seamlessly integrated with V-NAND, MEX/MGX controller, DRAM and software for high optimization. Like the 2.5" form factor model, the 850 EVO mSATA maximizes user experience with trace-based benchmark,



meaning that the 850 EVO mSATA provides form factor flexibility for SATA 6Gb/s interface by providing various yet standardized option. Therefore, you can enjoy Samsung's state-of-the-art technology no matter which form factor your device supports.

Reinforcement of TurboWrite Technology

Samsung was the first one to introduceTuboWrite Technology to sequential write performance in the early stages of the 840 EVO Series. With TurboWrite Technology, write speeds have been significantly accelerated during data transfer by creating a high-performance write buffer in an SSD. If a consecutive write operation (i.e. no idle time) exceeds the size of a buffer, the transfer will exit TurboWrite and be processed at "After TurboWrite" speeds. Once the buffer is cleared, the TurboWrite performance will resume. However, since the buffer size for TurboWrite is more than sufficient for everyday computer use, users can experience accelerated speeds for most workloads.

Guaranteed endurance and reliability for maximum use

Guaranteed endurance

The 850 EVO Series delivers guaranteed endurance and reliability by doubling the TeraBytes Written(TBW) compared to the previous generation 840 EVO Series backed by an industry leading 5 year warranty. With twice the endurance of a typical NAND flash SSD, the 850 EVO Series will keep working as long as you do. All form factors of the 850 EVO Series are guaranteed with a 5 year limited warranty or 75TBW for 120GB and 250GB, 150TBW for 500GB and 1TB.

Enhanced reliability with improved sustained performance

Through enhanced reliability with

improved sustained performance, the 850 EVO mSATA boasts long-term dependable performance of up to 40% longer than the 840 EVO Series with minimized performance degradation. You can use it every day when doing work or entertaining yourself knowing that it will keep performing even with heavy daily workloads over the years.

Advanced data encryption

Regardless of which form factor it is, the 850 EVO Series provides the same data encryption as the 840 EVO Series does. The Self-Encrypting Drive (SED) security technology will help keep your data safe at all times. The device is equipped with an AES 256-bit hardware-based encryption engine to ensure that your personal files remain A hardware-based secure. encryption without engine secures vour data performance degradation that you may software-based experience with а encryption. Furthermore, the 850 EVO mSATA is compliant with advanced security management solutions (TCG Opal and IEEE 1667). Magician will guide you on "How to use security features". Moreover, you can erase or initialize the data with the crypto erase service with PSID.

Efficient power management for all PC applications

Power consumption affects everyone. You actually save of up to 50% more on power than with the 840 EVO Series during write operations thanks to V-NAND consuming half the power of 2D planar NAND.

Plus, whether you would like to preserve battery life for longer cordless use or just save costs, power management is important. Device sleep signals the SSD to enter a low power state which is vital for ultra-books and other battery powered devices. With 850 EVO mSATA's Device Sleep feature at a highly efficient 2mW, you get longer battery life on your notebook thanks to a controller optimized for V-NAND. With the 850 EVO mSATA, you can work and play longer without having to plug in.

Technical Specifications

Samsung SSD 850 EVO mSATA					
Usage Application	Client PCs				
Capacity	120GB, 250GB, 500GB, 1TB(1,000GB)				
Dimensions (LxWxH)	(29.85±0.15) x (50.80±0.15) x Max 3.85 (mm)				
Interface	SATA 6Gb/s (compatible with SATA 3Gb/s and SATA 1.5Gb/s)				
Form Factor	mSATA				
Controller	Samsung MGX controller				
NAND Flash Memory	Samsung V-NAND Flash				
DRAM Cache Memory	512MB (120GB & 250GB & 500GB) LPDDR3 and 1GB (1TB) LPDDR3				
	Sequential Read: Max. 540 MB/s				
	Sequential Write**: Max. 520 MB/s				
	4KB Random Read (QD1): Max. 10,000 IOPS				
Performance*	4KB Random Write(QD1): Max. 40,000 IOPS				
	4KB Random Read(QD32): Max. 97,000 IOPS(250GB/500GB/1TB) Max. 95,000 IOPS(120GB)				
	4KB Random Write(QD32): Max. 88,000 IOPS				
	AES 256-bit Full Disk Encryption (FDE)				
Data Security	TCG/Opal V2.0, Encrypted Drive(IEEE1667)				
Weight	Max. 8.5g (1TB)				
Reliability	MTBF: 1.5 million hours				
TBW	120GB/250GB: 75TBW				
	500GB/1TB: 150 TBW				
Power	Active Read/Write (Average): Max. 2.3W(1TB) / Max.2.7W(1TB)				
Consumption***	Idle: Max. 50mW Device Sleep(Typ.): 2mW(120GB/250GB/500GB), 3mW(1TB)				
Supporting features	TRIM(Required OS support), Garbage Collection, S.M.A.R.T				
Temperature	Operating:0°C to 70°CNon-Operating:-40°C to 85°C				
Humidity	5% to 95%, non-condensing				
Vibration	Non-Operating: 20~2000Hz, 20G				
Shock	Non-Operating: 1500G , duration 0.5m sec, 3 axis				
Warranty	5 years limited				

* Sequential performance measurements based on CrystalDiskMark v.3.0.1. Random performance measurements based on lometer1.1.0

Performance may vary based on SSD's firmware version, system hardware & configuration. Test system configuration : Intel Core i7-4790K @ 4.0GHz, DDR3 1600MHz 8GB, OS – Windows7 Ultimate x64 SP1, IRST 13.0.3.1001, Chipset : Intel® Z97PRO

^{**} Sequential Write performance measurements based on TurboWrite technology., The sequential write performances after TurboWrite region are 150MB/s(120GB), 300MB/s(250GB) and 500MB/s(500GB). *** Power consumption measured with IOmeter 1.1.0 with Intel i7-4770K, DDR3 8GB, Intel®DH87RL OS- Windows7 Ultimate x64 SP1

Product Lineup

Density	Model Name	Box Contents	Model Code
120 GB*	MZ-M5E120	Samsung SSD 850 EVO mSATA 120GB Warranty statement	MZ-M5E120BW
250 GB*	MZ-M5E250	Samsung SSD 850 EVO mSATA 250GB Warranty statement	MZ-M5E250BW
500 GB*	MZ-M5E500	Samsung SSD 850 EVO mSATA 500GB Warranty statement	MZ-M5E500BW
1TB(1,000GB*)	MZ-M5E1T0	Samsung SSD 850 EVO mSATA 1TB Warranty statement	MZ-M5E1T0BW

* GB: 1GB = 1,000,000,000 bytes. A certain portion of capacity may be used for system file and maintenance use,

thus the actual capacity may differ that indicated on the product label.

For more information, please visit <u>www.samsung.com/ssd</u> and <u>www.samsungssd.com</u>. To download the latest software & manuals, please visit <u>www.samsung.com/samsungssd</u>

DISCLAIMER

SAMSUNG ELECTRONICS RESERVES THE RIGHT TO CHANGE PRODUCTS. INFORMATION AND SPECIFICATIONS WITHOUT NOTICE. Products and specifications discussed herein are for reference purposes only. All information discussed herein may change without notice and is provided on an "AS IS" basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppels or otherwise. Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply. For updates or additional information about Samsung products, contact your nearest Samsung office.

COPYRIGHT © 2016

This material is copyrighted by Samsung Electronics. Any unauthorized reproductions, use or disclosure of this material, or any part thereof, is strictly prohibited and is a violation under copyright law.

TRADEMARKS & SERVICE MARKS

The Samsung Logo is the trademark of Samsung Electronics. Adobe is a trademark and Adobe Acrobat is a registered trademark of Adobe Systems Incorporated. All other company and product names may be trademarks of the respective companies with which they are associated.

SAMSUNG